



202 DS OVEN - INDUSTRIAL SINGLE PHASE



CLEANING CONTRACTORS



WASTE TREATMENT - RECYCLING



TEXTILE



ADDITIVE MANUFACTURING



- ✓ Largest surface filter in its category
- ✓ Two powerful by pass motors with independent cooling
- ✓ Compact and mobile
- ✓ Easy filter replacement
- ✓ Accessory kit as standard
- ✓ Dustop filter cleaning system
- ✓ Easily removable container for safe disposal of collected material



SUCTION UNIT

Voltage	V - Hz	230 - 50
Power	kW	2,3
Max waterlift	mmH ₂ O	2500
Max waterlift	mmH ₂ O	2500
Max air flow	m ³ /h	360
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	76



FILTER UNIT

Filter Type		Cartridge
Surface - Diameter	cm ² -mm	30.000 - 360
Material - Efficiency	IEC 60335-2-69	Polyester - L
Air load on filter	m ³ /m ² /h	120
Cleaning system		Dustop



COLLECTION UNIT

Discharge system		Roll-out container
Transport capacity	kg/h	20



VOLUME

Dimensions	cm	59x48x110h
Weight	kg	35



SUCTION UNIT

The suction is provided by two by-pass motors, using carbon brushes, operated by independent switches and placed inside a sturdy steel casing, filled with soundproofing material.



FILTER UNIT

It is possible to clean the filter using an integrated mechanical system: an external lever shakes the filter vertically and enables to clean the filter thoroughly and safely, maintaining constant suction performance and preventing any dispersion of dust in the environment. Inside the filtering chamber there is a Nomex polyester filter resistant to temperatures up to 200 °



COLLECTION UNIT

The detachable steel collection tank has a quick release system for the rapid disposal of the sucked material.



OPTIONALS

- ✓ ABSOLUTE HEPA FILTER /H14
- ✓ ANTISTATIC FILTER CLASS M
- ✓ STAINLESS STEEL COLLECTION TANK
- ✓ STAINLESS STEEL TANK AND FILTER CHAMBER
- ✓ REMOTE CONTROL
- ✓ OTHER VOLTAGES AND FREQUENCIES AVAILABLE UPON REQUEST